

HSK - Hand Welding Extruders and Bending Technology

Hand welding extruder HSK18 GSX Pellet-Fed (Granulate)



BASIC EXTRUDER <ul style="list-style-type: none"> ▪ Extrusion welding from PE, PP, PVC ▪ temperature probe, location in the melt chamber ▪ Permanent speed control ▪ Control units for actual / desired mass and air temperature ▪ Cold start protection ▪ 1 pce nozzle blank included 		
TECHNICAL DATA		DIMENSIONS
Output	1.8 kg/h (4 lbs) (with PE granules)	600 x 200 x 430 mm
Heating extruder	500 W / air 2200 W	23.5 x 8 x 17 in
Drive	750 W	
Air requirement	300 l/min.	
Voltage	230V 50Hz or 120V 50/60Hz	
Weight	6.3 kg	
Guarantee	screw and cylinder 24 months	
HSK18 GSX (WITH HOT AIR BLOWER) <ul style="list-style-type: none"> ▪ Works as basic extruder, without external air supply ▪ Hot air blower controlled (air quantity 300 l/min) ▪ Technical data see basic extruder ▪ Heating hot air blower 2200 W 		
ADDITIONAL EQUIPMENT		
<ul style="list-style-type: none"> ▪ Welding nozzles ▪ Transportation box ▪ Granules 	<ul style="list-style-type: none"> Extruder nozzle preheating Prolongation Widen 	<ul style="list-style-type: none"> Angle adaptor Air compactor
Technical execution subject to modifications		