

HSK - Hand Welding Extruders and Bending Technology

Hand welding extruder HSK18 RSX /HSK18 RFX



BASIC EXTRUDER

- Extrusion welding from PE, PP, PVC
- temperature probe, location in the melt chamber
- rod feeding, no additional gearing
- Permanent speed control
- Control units for actual / desired mass and air temperature
- Cold start protection
- Rod diameter 3 and 4 mm
- 1 pce nozzle blank included

TECHNICAL DATA

Output	1.8 kg/h (4 lbs) (with PE rod 4 mm)
Heating extruder	500 W / air 2200 W
Drive	750 W
Air requirement	300 l/min.
Voltage	230V 50Hz or 120V 50/60Hz
Weight	5.3 kg
Guarantee	screw and cylinder 24 months

DIMENSIONS

450 x 140 x 260 mm
18 x 5.5 x 10 in

HSK18 RSX (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 2200 W

ADDITIONAL EQUIPMENT

▪ Welding nozzles	Extruder nozzle preheating	Angle adaptor
▪ Transportation box	Prolongation	Air compactor
▪ Welding rod	Widen	

Technical execution subject to modifications