

## HSK - Hand Welding Extruders and Bending Technology

### Hand welding extruder HSK26 GSX Pellet-Fed (Granulate)



#### BASIC EXTRUDER

- Extrusion welding from PE, PP, PVC and PVDF
- temperature probe, location in the melt chamber
- Control units for actual / desired mass and air temperature and actual speed
- Permanent speed control
- Cold start protection
- 1 pce nozzle blank included
- Speedcontrol

#### TECHNICAL DATA

Output	2.5 kg/h (with PE pellets)
Heating extruder	700W / air 2300W
Drive	740W
Air requirement	300 l/min
Voltage	230V 50Hz
Weight	7.4 kg or 16 lbs
Guarantee	Screw and cylinder 24 months

#### DIMENSIONS

600 x 200 x 430 mm
23.5 x 8 x 17 in

#### HSK26 GSX (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 2300W

#### ADDITIONAL EQUIPMENT

- |                      |                            |               |
|----------------------|----------------------------|---------------|
| ▪ Welding nozzles    | Extruder nozzle preheating | Angle adaptor |
| ▪ Transportation box | Prolongation               | Air compactor |
| ▪ Widen              |                            |               |

Technical execution subject to modifications