

## HSK - Hand Welding Extruders and Bending Technology

### Hand welding extruder HSK60 D /HSK60 DE



#### BASIC EXTRUDER

- Extrusion welding from PE, PP, PVC
- temperature probe, location in the melt chamber
- rod feeding, no additional gearing
- Permanent speed control
- Control units for actual / desired mass and air temperature
- Cold start protection
- Rod diameter 3,4 and 5 mm
- 1 pce nozzle blank included

#### TECHNICAL DATA

Output	6 kg/h (with PE rod 5mm)
Heating extruder	1200 W / air 3000 W
Drive	2000 W
Air requirement	300 l/min.
Voltage	3 x 230 V / 50Hz
Weight	11.4 kg
Guarantee	screw and cylinder 24 months

#### DIMENSIONS

680 x 155 x 340 mm
27 x 6 x 13 in

#### HSK60 DE (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 3000 W

#### ADDITIONAL EQUIPMENT

▪ Welding nozzles	Extruder nozzle preheating	Angle adaptor
▪ Transportation box	Prolongation	Air compactor
▪ Welding rod	Widen	

Technical execution subject to modifications.